



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

- Frequency Range: 2-4 GHz
- Directivity: 18dB Min.
- Frequency Sensitivity: ±0.75dB
- Power: 600 Watts
- VSWR: 1.20:1 Max.
- Insertion Loss: 0.40dB Max.

MATERIAL: _____		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 <a href="http://WWW.MCLI.COM">http://WWW.MCLI.COM</a>		SCALE:	N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE:	HIGH POWER DUAL DIRECTIONAL COUPLER
DRAWN:	DATE:	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		PART NO.:	HD3-30/NF
APPROVED:	DATE:			CAGE CODE:	SIZE:
Paiboon Luekhamhan	11-25-1997	0D2L5	A	N/A	80588
THIRD ANGLE PROJECTION 		DO NOT SCALE THE DRAWING			