



SPECIFICATIONS

FREQUENCY RANGE: 0.3–60 MHz
 INSERTION LOSS: 0.5dB Max.
 VSWR: 1.30:1 Max.
 ISOLATION: 35dB Min.
 PHASE BALANCE: ±1 Deg. Max.
 AMPLITUDE BALANCE: ±0.2dB Max.

MATERIAL:	
DRAWN:	DATE:
Paiboon Luekhamhan	03-14-2007
APPROVED:	DATE:
T. Nguyen	03-14-2007

MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC.
 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
 TEL: (727) 344-6254 FAX: (727) 381-6116
 http://WWW.MCLI.COM

SCALE:	N/A
SHEET:	N/A

UNLESS OTHERWISE SPECIFIED:
 TOLERANCES
 IN (INCHES) OR [mm] (MILLIMETERS)
 FRACTIONS: ± 1/64
 DECIMALS: ±.01 ±.005
 ANGLE: ±1/2°

DRAWING TITLE:
 2-WAY POWER DIVIDER

PART NO.
 PL2-1/PE

THIRD ANGLE PROJECTION

CAGE CODE:
 OD2L5

SIZE: A
 REV: N/A
 DO NOT SCALE THE DRAWING

DWG NO.
 82796