



ZONE		REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 1–12 GHz  
 Insertion Loss: 6.0dB Max.  
 Isolation: 15dB Min.  
 Power Handling: 10 Watts Max.  
 VSWR: 1.80:1 Max.  
 Amplitude Balance: ±2.0dB Max.  
 Phase Balance: ±12 Deg. Max.

DRAWING TITLE		32-WAY POWER DIVIDER	
PART NO.		PS32-12	
DRAWN: Pulsone Luskambeck	DATE: 04-08-2012	CAGE CODED: 002L5	SIZE: D
APPROVED: T. Nguyen	DATE: 04-08-2012	SCALE: N/A	DWG NO. 86492
MATERIAL:		DO NOT SCALE THE DRAWING	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.015 ANGLE: ± 1/2°		SHEET N/A	

**MCLI** MICROWAVE COMMUNICATIONS LABORATORIES INC.  
 7250 30TH AVE. N. SAINT PETERSBURG, FL 33710  
 TEL: (727) 344-8304 FAX: (727) 381-8116  
 WWW.MCLI.COM