



REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

**SPECIFICATIONS**

Frequency Range: 0.5–6.0 GHz  
 VSWR: 2.00:1 Max.  
 Amplitude Balance: ±1.4dB Max.  
 Phase Balance: ±7Deg. Max.  
 Insertion Loss: 4.9dB Max.  
 Isolation: 14dB Min.  
 Power: 20W (Load vswr @ 1.2)

MATERIAL:		<b>MCL</b> MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 544-6254 FAX: (727) 381-6116 <a href="http://www.mcll.com">http://www.mcll.com</a>	SCALE: N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ± 0.01 ± 0.005 ANGLE: ± 1/2°			DRAWING TITLE: <b>32-WAY POWER DIVIDER</b>
DRAWN: Paiboon		PART NO.: PS32-39/NF	
DATE: 11-05-2010		CAGE CODE: OD2L5	
APPROVED: T. Nguyen		DATE: 11-05-2010	
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLL)		SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING	DWG NO.: 86870